

Impact-S 4400

Specifications

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

Hardware specification	CPU: Intel® Xeon™ E5-2630v4 2.2GHz 25MB cache (will house dual CPU) Chipset: Intel® C612 Main memory: Up to 1TB ECC DDR4 2400MHz (8-slots) Video: ASPEED AST2400 BMC LAN: Dual Intel® i210, RTL8211E IPMI	Electromagnetic compatibility (EMC)	EN55032 Class A EN55024 Industrial severity (where applicable) Electrostatic discharge immunity test (EN61000-4-2) ±4kV Contact, applied to enclosure port ±8kV Air, applied to enclosure port ±4kV Indirect, applied to coupling plane Radiated, radio-frequency, electromagnetic field immunity test (EN61000-4-3) 80-1000MHz, 10 V/m (RMS, no modulation) 80% Modulation with 1kHz Sine wave Electrical fast transient/burst immunity test (EN61000-4-4) Power port AC, inc. protective earth Severity ±1kV Surge Immunity test (EN61000-4-5) Power port AC Severity ±1kV applied line to line Severity ±2kV applied line to earth Immunity to conducted disturbances induced by radio frequency fields (EN61000-4-6) Power port AC, inc. protective earth via CDN M3 0.15-80MHz, 10 V/m (no modulation) 80% Modulation with 1kHz Sine wave, applied via CDN type M3 Voltage dips, short interrupts and voltages variations immunity tests (EN61000-4-11) Power port AC >95% Reduction, 0.5 Periods >30% Reduction, 25 Periods >95% Reduction, 250 Periods Voltage dips, short interrupts and voltages variations immunity tests (EN61000-6-2) Power port AC >30% Reduction, 0.5 Periods >60% Reduction, 25 Periods >100% Reduction, 250 Periods Limits for harmonic current measurement (EN 61000-3-2), Product Class D Limitation of voltage changes, voltage fluctuations and flicker (EN 61000-3-3) Amplicon own a fully equipped EMC facility and can provide many additional tests to meet your requirements.
Disk capacity ¹	16 x 3.5" RAID Edition drives Configured as RAID 0, 1, 5, 10, 50, JBOD	Safety	Safety of information technology equipment (EN 60950) CE Marked
Hardware monitor	Independant thermal and fan speed monitoring hardware	Electrical Ratings	Industrial N+1 redundant design power supply Voltage: 90 ~ 264 VAC full range Frequency: 47 ~ 63Hz Inrush current: 40A / 60A (115 / 230VAC) PSU maximum secondary loading: 800W Active PFC EMI noise filter Over power/voltage/current protection Short circuit protection
System expansion ²	3 PCI-E 3.0 x8 1 PCI-E 3.0 x16 1 PCI-E 3.0 x4 (in x8) 1 PCI-E 2.0 x4 (in x8)		
Supported OS (Operating System)	Microsoft Server 2012R2, Server 2016, RHEL If your desired operating system is not listed, please contact us		
LEDs and switches	Front: Power (PC ON) LED Hard disk access LED LAN activity x 2 Drive caddy HDD activity and power LED x 16 System monitor x 2 LED and single alarm reset switch ATX system control switch, system reset Rear: System ON/OFF power switch x 3 (x 1 per module)		
External interfaces	2 x RJ45 Dual GbE 1 x RJ45 IPMI 1 x VGA 2 x USB 3.0 Type-A, 2 x USB 2.0 Type-A 1 x DB9 Serial		
Mechanical	Design: EIA RS-310C 19" Rackmount Standard Construction: Heavy duty cold rolled electroplated steel Colour: Black (custom colours available for large orders) Dimensions: 483 (W) x 177 (H) x 650 (D) mm (19.0" x 7.0" x 25.6") Packaging size: 854 (W) x 336 (H) x 576 (D) mm (33.6" x 13.2" x 22.7") Total drive capacity: 1 x Slim DVDROM, 2 x 2.5" internal, 1 x 2.5" Slim FDD, 16 x 3.5" hot-swap SATA/SAS bays Cooling : Industrial fans 3 x 120mm (90 CFM each) mid-chassis, 2 x 60mm (23.5CFM) rear Gross weight: approximately 40kg (fully populated)		
Environmental operational	Acoustic noise: Approximately 60dBA sound pressure at 23°C (typical) Temperature: 0 to 45°C (tested for extended operation up to 50°C) Humidity: 5 to 90% at 25°C non-condensing		
Environmental storage	Temperature: -20 to 65°C Humidity: 5 to 90% at 25°C non-condensing		

¹ Usable storage capacity will be less.

² All lanes available only with dual CPU